

NS-600 Series, 600Watt

FEATURES:

- ✓ Input voltage range 100-240VAC
- ✓ High reliability
- ✓ Built-in EMI filter
- ✓ Short circuit, over current, over voltage protections
- ✓ Cooling by free air convection
- ✓ 100% burn-in test
- ✓ With LED power indicator
- ✓ 4 year warranty



Model	Input voltage (Vac)	Output voltage (Vdc)	Output current (A)	Efficiency Typ.
NS600-3	100-240	3.3	100	80%
NS600-5		5	100	83%
NS600-9		9	66.5	86%
NS600-12		12	50	85%
NS600-15		15	40	87%
NS600-24		24	25	88%
NS600-48		48	12.5	84%

ELECTRICAL

Input						
Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units
Input voltage	V_{in}		90	--	264	Vac
			125	--	370	Vdc
Input frequency	F_{line}		47	--	63	Hz
Power factor	PF	Full voltage, full load	0.93	--	0.99	PF
Inrush current	I_{inrush}	Cold start, $V_{in}=115Vac$, full load	--	20	--	A
		Cold start, $V_{in}=230Vac$, full load	--	40	--	A
Input current	I_{in}	Full load, $V_{in}=115Vac$	--	7.2	--	A
		Full load, $V_{in}=230Vac$	--	3.6	--	A

NS-600 Series, 600Watt
ELECTRICAL
Output

Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units
Line regulation	$I_{out-line}$	--	--	1	--	%
Load regulation	$I_{out-load}$	V_{out} from min. to max.	--	1	--	%
Hold-on time	T_{on_hold}	Full load, $V_{in} = 115Vac$	--	17	--	ms
Turn-on delay time	T_{on_rise}	Full load, $V_{in} = 115Vac$	--	--	1	S
Ripple & noise	V_{ripple}	--	--	120	480	mV

Protection

Over current	Type: works at over 105%; it will recover automatically after fault condition is removed					
Short circuit	Hiccup mode, it will recover automatically after fault condition is removed					
Over voltage	Type: 110-150%; Locked mode, it will recover automatically after turn off the power					

Environment

Storage	$T_{storage}$	Humidity: 5% RH to 95% RH	-20	--	+75	°C
Ambient operating temperature	T_a	Startup at rated voltage (Required Derating)	-10	--	+65	°C
Operating relative humidity	H_a	Non condensing	10	--	95	%
MTBF	T_{MTBF}	Full load, 230Vac input, 25°C ambient temperature	--	--	200	kHrs
Dimension(LxWxH)	216 x 120 x 92mm					

Safety / EMC

Withstand voltage	I/P-O/P: 3KVac	I/P-FG: 2KVac	O/P-FG: 0.5KVac
Safety standards	UL, C-UL, CE, CB		
EMC	FCC Part 15, VCCI-A, CLSPR22-A, EN55022 Class A		
Harmonic Attenuator	IEC61000-3-2		

Notes: 1. Rated Load and Rated Input Voltage, $T_a = 25^\circ C$;

2. Ripple & Noise are measured at 20MHZ of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.

NS-600 Series, 600Watt

MECHANICAL

